W. A. Good

331 commonly used sections



# NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS



REPORT No. 315

# AERODYNAMIC CHARACTERISTICS OF AIRFOILS—VI

By

NATIONAL ADVISORY COMMITTEE
FOR AERONAUTICS



UNITED STATES
GOVERNMENT PRINTING OFFICE
WASHINGTON : 1929

## AERONAUTICAL SYMBOLS

### 1. FUNDAMENTAL AND DERIVED UNITS

| | Symbol | Metric | | English | |
|---|---|---|---|---|---|
| | | Unit | Symbol | Unit | Symbol |
| Length | $l$ | meter | m | foot (or mile) | ft. (or mi.) |
| Time | $t$ | second | sec | second (or hour) | sec. (or hr.) |
| Force | $F$ | weight of one kilogram | kg | weight of one pound | lb. |
| Power | $P$ | kg/m/sec | | horsepower | HP. |
| Speed | | km/hr | | mi./hr | M. P. H. |
| | | m/sec | | ft./sec | f. p. s. |

### 2. GENERAL SYMBOLS, ETC.

$W$, Weight, $=mg$

$g$, Standard acceleration of gravity $=9.80665$ m/sec.$^2=32.1740$ ft./sec.$^2$

$m$, Mass, $=\frac{W}{g}$

$\rho$, Density (mass per unit volume).

Standard density of dry air, 0.12497 (kg-m$^{-4}$ sec.$^2$) at 15° C and 760 mm $=0.002378$ (lb.-ft.$^{-4}$ sec.$^2$).

Specific weight of "standard" air, 1.2255 kg/m$^3=0.07651$ lb./ft.$^3$

$mk^2$, Moment of inertia (indicate axis of the radius of gyration, $k$, by proper subscript).

$S$, Area.

$S_w$, Wing area, etc.

$G$, Gap.

$b$, Span.

$c$, Chord length.

$b/c$, Aspect ratio.

$f$, Distance from $c.\ g.$ to elevator hinge.

$\mu$, Coefficient of viscosity.

### 3. AERODYNAMICAL SYMBOLS

$V$, True air speed.

$q$, Dynamic (or impact) pressure $=\frac{1}{2}\rho V^2$

$L$, Lift, absolute coefficient $C_L=\frac{L}{qS}$

$D$, Drag, absolute coefficient $C_D=\frac{D}{qS}$

$C$, Cross-wind force, absolute coefficient $C_C=\frac{C}{qS}$

$R$, Resultant force. (Note that these coefficients are twice as large as the old coefficients $L_C$, $D_C$.)

$i_w$ Angle of setting of wings (relative to thrust line).

$i_t$, Angle of stabilizer setting with reference to thrust line.

$\gamma$, Dihedral angle.

$\rho\frac{Vl}{\mu}$, Reynolds Number, where $l$ is a linear dimension.

e. g., for a model airfoil 3 in. chord, 100 mi./hr. normal pressure, 0° C: 255,000 and at 15° C., 230,000;

or for a model of 10 cm chord 40 m/sec, corresponding numbers are 299,000 and 270,000.

$C_p$, Center of pressure coefficient (ratio of distance of $C.\ P.$ from leading edge to chord length).

$\beta$, Angle of stabilizer setting with reference to lower wing, $=(i_t-i_w)$.

$\alpha$, Angle of attack.

$\epsilon$, Angle of downwash.

# REPORT No. 315

## AERODYNAMIC CHARACTERISTICS OF AIRFOILS—VI

### CONTINUATION OF REPORTS Nos. 93, 124, 182, 244, and 286

By

NATIONAL ADVISORY COMMITTEE
FOR AERONAUTICS

39331—29——1

## TABLE OF CONTENTS

# NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

NAVY BUILDING, WASHINGTON, D. C.

(An independent Government establishment, created by act of Congress approved March 3, 1915, for the supervision and direction of the scientific study of the problems of flight. It consists of 12 members who are appointed by the President, all of whom serve as such without compensation.)



## EXECUTIVE COMMITTEE

# REPORT No. 315

## AERODYNAMIC CHARACTERISTICS OF AIRFOILS—VI

CONTINUATION OF REPORTS NOS. 93, 124, 182, 244, AND 286

By National Advisory Committee for Aeronautics

### INTRODUCTION

This collection of data on airfoils has been made from the published reports of a number of the leading aerodynamic laboratories of this country and Europe.[1] The information which was originally expressed according to the different customs of the several laboratories is here presented in a uniform series of charts and tables suitable for the use of designing engineers and for purposes of general reference.

It is a well-known fact that the results obtained in different laboratories, because of their individual methods of testing, are not strictly comparable even if proper scale corrections for size of model and speed of test are supplied. It is, therefore, unwise to compare too closely the coefficients of two wing sections tested in different laboratories. Tests of different wing sections from the same source, however, may be relied on to give true relative values.

The absolute system of coefficients has been used, since it is thought by the National Advisory Committee for Aeronautics that this system is the one most suited for international use and yet it is one from which a desired transformation can be easily made. For this purpose a set of transformation constants is given.

Each airfoil section is given a reference number, and the test data are presented in the form of curves from which the coefficients can be read with sufficient accuracy for designing purposes. The dimensions of the profile of each section are given at various stations along the chord in per cent of the chord length, the latter also serving as the datum line. The shape of the section is also shown with reasonable accuracy in order to enable one to more clearly visualize the section under consideration, the outside of the heavy line representing the profile.

The authority for the results here presented is given as the name of the laboratory at which the experiments were conducted, as explained under abbreviations, with the size of model, wind velocity, and year of test.

### TRANSFORMATION CONSTANTS

For the convenience of those who prefer to use a system of units other than the absolute system, there is given below a table of transformation constants based on the standard condition adopted by the National Advisory Committee for Aeronautics of—

| | | |
|---|---|---|
| Temperature | = 15° C | = 59° F. |
| Pressure | = 760 mm Hg | = 29.92 in. Hg. |
| Humidity | = 0 | |
| Gravity | = 9.80665 m/s² | = 32.1740 ft./sec.² |

thus giving values of specific weight of air

$$W = 1.2255 \text{ kg/m}^3 = 0.07651 \text{ lb./cu. ft.}$$

[1] A previous collection of airfoil sections numbered 1 to 759 and Charts 1 to 20 may be found in N. A. C. A. Reports Nos. 93, 124, 182, 244, and 286.

and of density

$\rho = 0.12497$ kg-m$^{-4}$s$^2$ in the French engineering or kilogram, meter, second system.

Or

$\rho = 0.002378$ lb.-ft.$^{-4}$sec.$^2$ in the English or pound, foot, second system.

| | |
|---|---|
| In absolute units | $P = CV^2\rho/2$ |
| In kg/m$^2$ (m/s) | $P = .0625\ CV^2$ |
| In kg/m$^2$ (km/h) | $P = .004822\ CV^2$ |
| In lb./sq. ft. (ft./sec.) | $P = .001189\ CV^2$ |
| In lb./sq. ft. (mi./hr.) | $P = .002558\ CV^2$ |

(Note that these constants are half as large as those used in Reports Nos. 93 and 124 and that the absolute coefficients used in this report are twice as large as the old coefficients. See Report No. 240 regarding change in absolute coefficients.)

## INDEX

Four separate types of indexes are given—chart indexes which make it possible for a designer to select the wing section most suitable for the particular design in which he is interested; a group index which is arranged by countries and laboratories at which tests were conducted, each section also being designated by a reference number; an index of abbreviations, used on the characteristic sheets, to indicate the laboratories at which the tests were made; and an alphabetical index.

## CHART INDEX

In order that the designer may easily pick out a wing section which is suited to the type of airplane on which he is working, four index charts are given which classify the wings according to their aerodynamic and structural properties. In the charts of this report a lower-case letter is placed adjacent to the reference number giving $Vl$ values, so that a comparison can be made without referring to the individual drawings. In this value $V$ represents the wind velocity in feet per second and $l$ a linear dimension, the chord length in feet.

In chart No. 21 the minimum drag $C_D$, is plotted against the $L/D$ at one-fourth the maximum lift $C_L$. This chart should be used in choosing a wing section for a high-speed airplane, the wing sections being more suited for this use the farther they are from the lower left-hand corner.

In chart No. 22 the mean spar depth is plotted against the maximum lift $C_L$, in order to show the possible strength and lightness of the wing structure. The higher the maximum lift coefficient is, the smaller will be the wing area and the lighter the structural weight, and in the same way the greater the depth of the spars the lighter will be their weight, so that the sections the greatest distance from the lower left-hand corner will give the lightest and strongest wings. The "mean spar depth" is obtained by assuming the spars to be located, respectively, at 15 and 60 per cent of the chord, and by dividing the sum of their thicknesses, in per cent of chord length at these points, by 2.

In chart No. 23 the maximum $L/D$ is plotted against the maximum lift $C_L$, which is of use in choosing the wing section for a slow and efficient airplane. In the same way as before the sections farthest from the lower left-hand corner are the best for this purpose.

In chart No. 24 the $L/D$ at two-thirds the maximum lift $C_L$, is plotted against the maximum lift $C_L$. This chart can be used for choosing a section that will give an efficient climb or a long range at cruising speed. The best sections for this purpose will be farthest from the lower left-hand corner of the chart.

## CHART INDEX



## INDEX OF ABBREVIATIONS

| Name of laboratory at which tests were made | Abbreviations used on figures |
|---|---|
| Langley Memorial Aeronautical Laboratory of the National Advisory Committee for Aeronautics, U. S. A. | L. M. A. L. |
| Washington Navy Yard, U. S. A. | W. N. Y. |
| Engineering Division, McCook Field, U. S. A. | McC. F. |
| Ergebnisse der Aerodynamischen Versuchsanstalt zu Göttingen, Germany | Göttingen. |
| Service Technique de l'Aéronautique, France | S. T. Aé. |
| Laboratoire Aerotechnique de Rhode St. Genese-Bruxelles, Belgium | Rhode St. Genese. |
| Instituto Sperimentale Aeronautico, Italy | I. S. A. |

# GROUP INDEX

| Airfoil | Wind tunnel where tested | Report reference number |
|---|---|---|
| UNITED STATES | | |
| U. S. N. P. S. 1 | L. M. A. L. | 760 |
| U. S. N. P. S. 2 | do | 761 |
| U. S. N. P. S. 3 | do | 762 |
| U. S. N. P. S. 4 | do | 763 |
| U. S. N. P. S. 5 | do | 764 |
| U. S. N. P. S. 6 | do | 765 |
| Martin M-I | W. N. Y. | 766 |
| Martin M-II | do | 767 |
| Martin M-III | do | 768 |
| R-3 (Root section) | McC. F. | 769 |
| U. S. A. 45M | do | 770 |
| GERMANY | | |
| Göttingen 359 | Göttingen | 771 |
| Göttingen 361 | do | 772 |
| Göttingen 362 | do | 773 |
| Göttingen 368 | do | 774 |
| Göttingen 369 | do | 775 |
| Göttingen 371 | do | 776 |
| Göttingen 372 | do | 777 |
| Göttingen 373 | do | 778 |
| Göttingen 374 | do | 779 |
| Göttingen 375 | do | 780 |
| Göttingen 377 | do | 781 |
| Göttingen 392 | do | 782 |
| Göttingen 397 | do | 783 |
| Göttingen 399 | do | 784 |
| Göttingen 401 | do | 785 |
| Göttingen 402 | do | 786 |
| Göttingen 403 | do | 787 |
| Göttingen 408 | do | 788 |
| Göttingen 417 | do | 789 |
| Göttingen 428 | do | 790 |
| Göttingen 437 | do | 791 |
| Göttingen 438 | do | 792 |
| Göttingen 439 | do | 793 |
| Göttingen 442 | do | 794 |
| Göttingen 443 | do | 795 |
| Göttingen 444 | do | 796 |
| Göttingen 445 | do | 797 |
| FRANCE | | |
| Eiffel 359 (Nieuport Astra) | S. T. Aé. Lab. | 798 |
| Eiffel 386 (S. T. Ae.) | do | 799 |
| Eiffel 387 (S. T. Aé.) | do | 800 |
| Eiffel 402 (Pescara) | do | 801 |
| Eiffel 429 (Lachassagne) | do | 802 |
| Eiffel 432 (Lachassagne) | do | 803 |
| Eiffel 433a (Chalambel) | do | 804 |
| Eiffel 438 (Lachassagne) | do | 805 |
| St. Cyr 152 (Royer) | do | 806 |
| St. Cyr 153 (Royer) | do | 807 |
| St. Cyr 156 (Royer) | do | 808 |
| St. Cyr 157 (Royer) | do | 809 |
| FRANCE—continued | | |
| St. Cyr 162 (Royer) | S. T. Aé. Lab. | 810 |
| St. Cyr 170 (Royer) | do | 811 |
| St. Cyr 174 (Royer) | do | 812 |
| St. Cyr 233 (Bartel 37-Ib) | do | 813 |
| St. Cyr 235 (Bartel 37-Ic) | do | 814 |
| St. Cyr 237 (Bartel 15-Ic) | do | 815 |
| St. Cyr 239 (Bartel 37-IIa) | do | 816 |
| St. Cyr 240 (Bartel 37-IIb) | do | 817 |
| St. Cyr 242 (Bartel 57-IIc) | do | 818 |
| St. Cyr 243 (Bartel 37-IIIc) | do | 819 |
| BELGIUM | | |
| Rhode St. Genese 1 | Rhode St. Genese | 820 |
| Rhode St. Genese 2 | do | 821 |
| Rhode St. Genese 16 | do | 822 |
| Rhode St. Genese 17 | do | 823 |
| Rhode St. Genese 19 | do | 824 |
| Rhode St. Genese 26 | do | 825 |
| Rhode St. Genese 29 | do | 826 |
| Rhode St. Genese 31 | do | 827 |
| Rhode St. Genese 33 | do | 828 |
| Rhode St. Genese 35 | do | 829 |
| Rhode St. Genese 37 | do | 830 |
| ITALY | | |
| I. S. A. 334 | I. S. A. | 831 |
| I. S. A. 390 | do | 832 |
| I. S. A. 472 | do | 833 |
| I. S. A. 500 | do | 834 |
| I. S. A. 501 | do | 835 |
| I. S. A. 502 | do | 836 |
| I. S. A. 507 | do | 837 |
| I. S. A. 605 | do | 838 |
| I. S. A. 663 | do | 839 |
| I. S. A. 693 | do | 840 |
| I. S. A. 695 | do | 841 |
| I. S. A. 768 | do | 842 |
| I. S. A. 776 | do | 843 |
| I. S. A. 801 | do | 844 |
| I. S. A. 803 | do | 845 |
| I. S. A. 804 | do | 846 |
| I. S. A. 805 | do | 847 |
| I. S. A. 806 | do | 848 |
| I. S. A. 807 | do | 849 |
| I. S. A. 809 | do | 850 |
| I. S. A. 812 | do | 851 |
| I. S. A. 820 | do | 852 |
| I. S. A. 821 | do | 853 |
| I. S. A. 829 | do | 854 |
| I. S. A. 858 | do | 855 |
| I. S. A. 881a | do | 856 |
| I. S. A. 881b | do | 857 |
| I. S. A. 881c | do | 858 |
| I. S. A. 911 | do | 859 |

# ALPHABETICAL INDEX




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.40 | 0.40 |
| 1¼ | 1.10 | 0.00 |
| 2½ | 1.64 | 0.00 |
| 5 | 2.36 | 0.00 |
| 7½ | 2.83 | 0.00 |
| 10 | 3.16 | 0.00 |
| 15 | 3.58 | 0.00 |
| 20 | 3.80 | 0.00 |
| 30 | 3.99 | 0.00 |
| 40 | 3.96 | 0.00 |
| 50 | 3.80 | 0.00 |
| 60 | 3.48 | 0.00 |
| 70 | 2.96 | 0.00 |
| 80 | 2.24 | 0.00 |
| 90 | 1.42 | 0.00 |
| 95 | 0.98 | 0.00 |
| 100 | 0.31 | 0.00 |




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.80 | 0.80 |
| 1¼ | 2.30 | 0.00 |
| 2½ | 3.28 | 0.00 |
| 5 | 4.72 | 0.00 |
| 7½ | 5.66 | 0.00 |
| 10 | 6.32 | 0.00 |
| 15 | 7.16 | 0.00 |
| 20 | 7.60 | 0.00 |
| 30 | 7.98 | 0.00 |
| 40 | 7.92 | 0.00 |
| 50 | 7.60 | 0.00 |
| 60 | 6.96 | 0.00 |
| 70 | 5.92 | 0.00 |
| 80 | 4.48 | 0.00 |
| 90 | 3.82 | 0.00 |
| 95 | 1.97 | 0.00 |
| 100 | 0.62 | 0.00 |




| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.00 | 1.00 |
| 1¼ | 2.80 | 0.00 |
| 2½ | 4.10 | 0.00 |
| 5 | 5.90 | 0.00 |
| 7½ | 7.08 | 0.00 |
| 10 | 7.90 | 0.00 |
| 15 | 8.35 | 0.00 |
| 20 | 9.50 | 0.00 |
| 30 | 9.98 | 0.00 |
| 40 | 9.90 | 0.00 |
| 50 | 9.50 | 0.00 |
| 60 | 8.70 | 0.00 |
| 70 | 7.40 | 0.00 |
| 80 | 5.60 | 0.00 |
| 90 | 3.52 | 0.00 |
| 95 | 2.46 | 0.00 |
| 100 | 0.92 | 0.00 |




| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.20 | 1.20 |
| 1¼ | 3.40 | 0.00 |
| 2½ | 4.92 | 0.00 |
| 5 | 7.08 | 0.00 |
| 7½ | 8.50 | 0.00 |
| 10 | 9.48 | 0.00 |
| 15 | 10.74 | 0.00 |
| 20 | 11.40 | 0.00 |
| 30 | 11.98 | 0.00 |
| 40 | 11.98 | 0.00 |
| 50 | 11.40 | 0.00 |
| 60 | 10.44 | 0.00 |
| 70 | 8.88 | 0.00 |
| 80 | 6.72 | 0.00 |
| 90 | 4.23 | 0.00 |
| 95 | 2.95 | 0.00 |
| 100 | 0.77 | 0.00 |

REFERENCE NO. 764




| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.60 | 1.60 |
| 1¼ | 4.75 | 0.00 |
| 2½ | 6.56 | 0.00 |
| 5 | 9.44 | 0.00 |
| 7½ | 11.33 | 0.00 |
| 10 | 12.65 | 0.00 |
| 15 | 14.32 | 0.00 |
| 20 | 15.20 | 0.00 |
| 30 | 15.97 | 0.00 |
| 40 | 15.84 | 0.00 |
| 50 | 15.20 | 0.00 |
| 60 | 13.92 | 0.00 |
| 70 | 11.84 | 0.00 |
| 80 | 8.96 | 0.00 |
| 90 | 5.80 | 0.00 |
| 95 | 3.94 | 0.00 |
| 100 | 1.23 | 0.00 |
| Max. Ord. 16.00 | | |

REFERENCE NO. 765




| % | UP'R | LW'R |
|---|---|---|
| 0 | 2.00 | 2.00 |
| 1¼ | 5.75 | 0.00 |
| 2½ | 8.20 | 0.00 |
| 5 | 11.80 | 0.00 |
| 7½ | 14.16 | 0.00 |
| 10 | 15.60 | 0.00 |
| 15 | 17.90 | 0.00 |
| 20 | 19.00 | 0.00 |
| 30 | 19.98 | 0.00 |
| 40 | 19.80 | 0.00 |
| 50 | 19.00 | 0.00 |
| 60 | 17.40 | 0.00 |
| 70 | 14.80 | 0.00 |
| 80 | 11.20 | 0.00 |
| 90 | 7.04 | 0.00 |
| 95 | 4.92 | 0.00 |
| 100 | 1.54 | 0.00 |
| Max. Ord. 20.00 | | |

REFERENCE NO. 766




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.00 | 0.00 |
| 1¼ | 1.20 | -1.20 |
| 2½ | 1.50 | -1.50 |
| 5 | 1.90 | -1.90 |
| 7½ | 2.30 | -2.30 |
| 10 | 2.70 | -2.70 |
| 15 | 3.32 | -3.32 |
| 20 | 3.80 | -3.80 |
| 30 | 4.40 | -4.40 |
| 40 | 4.20 | -4.20 |
| 50 | 4.00 | -4.00 |
| 60 | 3.40 | -3.40 |
| 70 | 2.70 | -2.70 |
| 80 | 2.00 | -2.00 |
| 90 | 1.10 | -1.10 |
| 95 | 0.80 | -0.80 |
| 100 | 0.00 | -0.00 |

REFERENCE NO. 767




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.00 | 0.00 |
| 1¼ | 0.90 | -0.85 |
| 2½ | 1.18 | -1.05 |
| 5 | 1.68 | -1.40 |
| 7½ | 2.12 | -1.70 |
| 10 | 2.50 | -2.00 |
| 15 | 3.00 | -2.55 |
| 20 | 3.50 | -3.10 |
| 30 | 4.10 | -3.70 |
| 40 | 4.10 | -3.70 |
| 50 | 3.70 | -3.30 |
| 60 | 3.20 | -2.50 |
| 70 | 2.70 | -2.00 |
| 80 | 2.00 | -1.50 |
| 90 | 1.00 | -1.00 |
| 95 | 0.55 | -0.55 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 768

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.00 | 0.00 |
| 1¼ | 1.08 | - .95 |
| 2½ | 1.30 | -1.02 |
| 5 | 1.75 | -1.20 |
| 7½ | 2.18 | -1.35 |
| 10 | 2.50 | -1.50 |
| 15 | 3.22 | -1.80 |
| 20 | 3.70 | -2.00 |
| 30 | 4.30 | -2.10 |
| 40 | 4.00 | -2.20 |
| 50 | 3.70 | -2.00 |
| 60 | 3.20 | -1.70 |
| 70 | 2.60 | -1.30 |
| 80 | 2.00 | -1.00 |
| 90 | 1.00 | -0.70 |
| 95 | 0.60 | -0.45 |
| 100 | 0.00 | 0.00 |




REFERENCE NO. 769

| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.57 | 1.57 |
| 1¼ | 3.54 | 0.00 |
| 2½ | 4.57 | -0.83 |
| 5 | 6.30 | -1.33 |
| 7½ | 7.60 | -1.87 |
| 10 | 8.70 | -2.40 |
| 15 | 10.27 | -3.27 |
| 20 | 11.27 | -3.98 |
| 30 | 12.38 | -4.73 |
| 40 | 12.38 | -4.73 |
| 50 | 11.68 | -4.47 |
| 60 | 10.32 | -3.80 |
| 70 | 8.60 | -3.13 |
| 80 | 6.60 | -2.33 |
| 90 | 4.33 | -1.17 |
| 95 | 3.08 | -0.60 |
| 100 | 0.30 | +0.90 |




REFERENCE NO. 770

| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.30 | 1.30 |
| 1¼ | 3.20 | 0.20 |
| 2½ | 4.25 | -0.18 |
| 5 | 5.37 | -0.56 |
| 7½ | 7.27 | -0.85 |
| 10 | 8.17 | -1.03 |
| 15 | 9.35 | -1.30 |
| 20 | 9.98 | -1.43 |
| 30 | 10.05 | -1.58 |
| 40 | 9.23 | -1.60 |
| 50 | 8.10 | -1.58 |
| 60 | 6.75 | -1.43 |
| 70 | 5.23 | -1.20 |
| 80 | 3.58 | -0.87 |
| 90 | 1.83 | -0.48 |
| 95 | 0.98 | -0.23 |
| 100 | 0.00 | 0.00 |




REFERENCE NO. 771

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.75 | 0.75 |
| 1¼ | 2.50 | 0.00 |
| 2½ | 3.60 | 0.00 |
| 5 | 5.30 | 0.20 |
| 7½ | 6.55 | 0.45 |
| 10 | 7.45 | 0.75 |
| 15 | 8.75 | 1.30 |
| 20 | 9.55 | 1.75 |
| 30 | 10.25 | 2.45 |
| 40 | 10.00 | 2.85 |
| 50 | 9.15 | 2.55 |
| 60 | 7.85 | 2.35 |
| 70 | 6.25 | 1.85 |
| 80 | 4.40 | 1.25 |
| 90 | 2.80 | 0.60 |
| 95 | 1.50 | 0.30 |
| 100 | 0.15 | 0.15 |



REFERENCE NO. 772




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.85 | 0.85 |
| 1¼ | 2.55 | 0.00 |
| 2½ | 3.40 | 0.10 |
| 5 | 4.90 | 0.40 |
| 7½ | 6.05 | 0.75 |
| 10 | 6.95 | 1.10 |
| 15 | 8.30 | 1.75 |
| 20 | 8.95 | 2.15 |
| 30 | 9.35 | 2.85 |
| 40 | 9.00 | 3.15 |
| 50 | 8.20 | 3.25 |
| 60 | 7.00 | 3.05 |
| 70 | 5.60 | 2.60 |
| 80 | 4.00 | 2.00 |
| 90 | 2.15 | 1.05 |
| 95 | 1.20 | 0.50 |
| 100 | 0.10 | 0.10 |

REFERENCE NO. 773




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.60 | 0.60 |
| 1¼ | 2.65 | 0.10 |
| 2½ | 3.55 | 0.00 |
| 5 | 4.75 | 0.05 |
| 7½ | 5.55 | 0.25 |
| 10 | 6.40 | 0.55 |
| 15 | 7.50 | 1.05 |
| 20 | 8.20 | 1.60 |
| 30 | 8.75 | 2.35 |
| 40 | 8.50 | 2.80 |
| 50 | 7.85 | 2.95 |
| 60 | 6.75 | 2.80 |
| 70 | 5.40 | 2.30 |
| 80 | 3.80 | 1.80 |
| 90 | 2.00 | 0.90 |
| 95 | 1.05 | 0.45 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 774




| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.70 | 1.70 |
| 1¼ | 3.05 | 1.15 |
| 2½ | 4.15 | 0.70 |
| 5 | 5.60 | 0.25 |
| 7½ | [illegible] | [illegible] |
| 10 | 7.40 | 0.05 |
| 15 | 8.15 | 0.45 |
| 20 | 8.45 | 1.00 |
| 30 | 8.35 | 1.65 |
| 40 | 7.70 | 1.80 |
| 50 | 6.80 | 1.60 |
| 60 | 5.55 | 1.30 |
| 70 | 4.30 | 0.95 |
| 80 | 2.90 | 0.65 |
| 90 | 1.60 | 0.35 |
| 95 | 0.95 | 0.20 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 775




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.10 | 0.10 |
| 1¼ | 2.50 | 0.00 |
| 2½ | 3.50 | 0.25 |
| 5 | 4.95 | 0.60 |
| 7½ | 5.60 | 1.00 |
| 10 | 6.25 | 1.35 |
| 15 | 7.15 | 1.85 |
| 20 | 7.80 | 2.30 |
| 30 | 8.35 | 2.50 |
| 40 | 8.25 | 2.65 |
| 50 | 7.50 | [illegible] |
| 60 | 6.25 | 2.05 |
| 70 | 4.80 | 1.50 |
| 80 | 3.30 | 1.00 |
| 90 | 1.80 | 0.50 |
| 95 | 0.95 | 0.20 |
| 100 | 0.00 | 0.00 |

REFERENCE, NO. 776




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.75 | 0.75 |
| 1¼ | 2.50 | 0.00 |
| 2½ | 3.40 | 0.00 |
| 5 | 4.60 | 0.10 |
| 7½ | 5.50 | 0.25 |
| 10 | 6.20 | 0.45 |
| 15 | 7.15 | 0.80 |
| 20 | 7.80 | 1.10 |
| 30 | 8.50 | 1.55 |
| 40 | 8.35 | 1.85 |
| 50 | 7.80 | 1.95 |
| 60 | 6.95 | 1.85 |
| 70 | 5.55 | 1.55 |
| 80 | 3.95 | 1.15 |
| 90 | 2.15 | 0.60 |
| 95 | 1.15 | 0.30 |
| 100 | 0.10 | 0.10 |

Name of section: Göttingen 371
Size of model: 39.37" x 7.874"
Wind velocity: 98.4 ft./sec.
Where tested: Göttingen Date: 1919

REFERENCE NO. 777




| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.25 | 1.25 |
| 1¼ | 2.25 | 0.35 |
| 2½ | 2.95 | 0.10 |
| 5 | 4.05 | 0.00 |
| 7½ | 4.95 | 0.15 |
| 10 | 5.60 | 0.35 |
| 15 | 6.65 | 0.80 |
| 20 | 7.15 | 1.20 |
| 30 | 8.00 | 1.60 |
| 40 | 8.05 | 2.15 |
| 50 | 7.50 | 2.20 |
| 60 | 6.65 | 2.00 |
| 70 | 5.35 | 1.65 |
| 80 | 3.80 | 1.20 |
| 90 | 2.10 | 0.60 |
| 95 | 1.15 | 0.30 |
| 100 | 0.10 | 0.10 |

Name of section: Göttingen 372
Size of model: 39.37" x 7.874"
Wind velocity: 98.4 ft./sec.
Where tested: Göttingen Date: 1919

REFERENCE NO. 778




| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.00 | 1.00 |
| 1¼ | 2.65 | 0.00 |
| 2½ | 3.75 | 0.30 |
| 5 | 5.15 | 0.65 |
| 7½ | 6.15 | 1.00 |
| 10 | 6.90 | 1.30 |
| 15 | 7.90 | 1.75 |
| 20 | 8.60 | 2.15 |
| 30 | 9.00 | 2.50 |
| 40 | 8.70 | 2.65 |
| 50 | 7.85 | 2.50 |
| 60 | 6.75 | 2.25 |
| 70 | 5.30 | 1.85 |
| 80 | 3.70 | 1.25 |
| 90 | 2.00 | 0.65 |
| 95 | 1.05 | 0.30 |
| 100 | 0.00 | 0.00 |

Name of section: Göttingen 373
Size of model: 39.37" x 7.874"
Wind velocity: 98.4 ft./sec.
Where tested: Göttingen Date: 1919

REFERENCE NO. 779




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.55 | 0.55 |
| 1¼ | 2.30 | 0.15 |
| 2½ | 3.35 | 0.40 |
| 5 | 4.75 | 0.70 |
| 7½ | 5.70 | 0.95 |
| 10 | 6.35 | 1.15 |
| 15 | 7.30 | 1.35 |
| 20 | 7.85 | 1.55 |
| 30 | 8.15 | 1.70 |
| 40 | 7.75 | 1.70 |
| 50 | 7.05 | 1.60 |
| 60 | 6.00 | 1.30 |
| 70 | 4.85 | 1.00 |
| 80 | 3.40 | 0.65 |
| 90 | 1.80 | 0.30 |
| 95 | 0.95 | 0.10 |
| 100 | 0.05 | 0.05 |

Name of section: Göttingen 374
Size of model: 39.37" x 7.874"
Wind velocity: 98.4 ft./sec.
Where tested: Göttingen Date: 1919

REFERENCE NO. 780

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.55 | 0.56 |
| 1¼ | 2.65 | 0.15 |
| 2½ | 3.75 | 0.50 |
| 5 | 5.25 | 0.95 |
| 7½ | 6.25 | 1.10 |
| 10 | 6.90 | 1.25 |
| 15 | 7.70 | 1.40 |
| 20 | 8.05 | 1.55 |
| 30 | 8.15 | 1.65 |
| 40 | 7.70 | 1.60 |
| 50 | 8.95 | 1.50 |
| 60 | 6.00 | 1.30 |
| 70 | 4.75 | 1.00 |
| 80 | 3.25 | 0.60 |
| 90 | 1.80 | 0.35 |
| 95 | 1.00 | 0.15 |
| 100 | 0.10 | 0.10 |




REFERENCE NO. 781

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.75 | 0.75 |
| 1¼ | 2.20 | 0.00 |
| 2½ | 3.00 | 0.00 |
| 5 | 4.10 | 0.10 |
| 7½ | 5.00 | 0.25 |
| 10 | 5.65 | 0.40 |
| 15 | 6.60 | 0.65 |
| 20 | 7.15 | 0.90 |
| 30 | 7.60 | 1.15 |
| 40 | 7.55 | 1.25 |
| 50 | 7.05 | 1.05 |
| 60 | 6.25 | 0.75 |
| 70 | 5.15 | 0.55 |
| 80 | 3.75 | 0.30 |
| 90 | 2.05 | 0.10 |
| 95 | 1.15 | 0.05 |
| 100 | 0.15 | 0.15 |




REFERENCE NO. 782

| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.40 | 1.40 |
| 1¼ | 2.50 | 0.85 |
| 2½ | 3.25 | 0.70 |
| 5 | 4.65 | 0.45 |
| 7½ | 5.75 | 0.25 |
| 10 | 6.70 | 0.15 |
| 15 | 8.25 | 0.00 |
| 20 | 9.40 | 0.00 |
| 30 | 10.45 | 0.30 |
| 40 | 10.50 | 0.95 |
| 50 | 9.90 | 1.00 |
| 60 | 8.60 | 1.15 |
| 70 | 6.95 | 1.20 |
| 80 | 5.00 | 1.00 |
| 90 | 2.85 | 0.65 |
| 95 | 1.55 | 0.30 |
| 100 | 0.00 | 0.00 |




REFERENCE NO. 783

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.75 | 0.75 |
| 1¼ | 2.05 | 0.00 |
| 2½ | 2.55 | 0.00 |
| 5 | 3.45 | 0.20 |
| 7½ | 4.10 | 0.40 |
| 10 | 4.65 | 0.65 |
| 15 | 5.55 | 1.10 |
| 20 | 6.25 | 1.40 |
| 30 | 6.90 | 1.80 |
| 40 | 6.95 | 1.95 |
| 50 | 6.55 | 1.80 |
| 60 | 5.60 | 1.55 |
| 70 | 4.45 | 1.15 |
| 80 | 3.05 | 0.75 |
| 90 | 1.65 | 0.35 |
| 95 | 0.90 | 0.15 |
| 100 | 0.10 | 0.10 |



REFERENCE NO. 784

N.A.C.A.

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.95 | 0.95 |
| 1¼ | 2.50 | 0.15 |
| 2½ | 3.45 | 0.00 |
| 5 | 4.25 | 0.05 |
| 7½ | 5.10 | 0.25 |
| 10 | 5.80 | 0.45 |
| 15 | 6.95 | 0.75 |
| 20 | 7.65 | 1.05 |
| 30 | 8.30 | 1.40 |
| 40 | 8.15 | 1.55 |
| 50 | 7.60 | 1.55 |
| 60 | 6.60 | 1.45 |
| 70 | 5.25 | 1.10 |
| 80 | 3.75 | 0.80 |
| 90 | 2.05 | 0.40 |
| 95 | 1.1u | 0.20 |
| 100 | 0.15 | 0.15 |




REFERENCE NO. 785

N.A.C.A.

| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.25 | 1.25 |
| 1¼ | 3.15 | 0.05 |
| 2½ | 4.05 | 0.00 |
| 5 | 5.30 | 0.15 |
| 7½ | 6.35 | 0.45 |
| 10 | 7.20 | 0.80 |
| 15 | 8.35 | 1.50 |
| 20 | 9.00 | 2.00 |
| 30 | 9.35 | 2.25 |
| 40 | 8.85 | 2.20 |
| 50 | 8.05 | 1.95 |
| 60 | 6.90 | 1.55 |
| 70 | 5.45 | 1.20 |
| 80 | 3.85 | 0.80 |
| 90 | 2.20 | 0.40 |
| 95 | 1.35 | 0.20 |
| 100 | 0.20 | 0.20 |




REFERENCE NO. 786

N.A.C.A.

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.60 | 0.60 |
| 1¼ | 2.60 | 0.15 |
| 2½ | 3.65 | 0.30 |
| 5 | 5.05 | 0.70 |
| 7½ | 6.30 | 1.05 |
| 10 | 7.00 | 1.35 |
| 15 | 8.35 | 1.80 |
| 20 | 9.10 | 2.30 |
| 30 | 9.55 | 2.85 |
| 40 | 9.20 | 2.95 |
| 50 | 8.30 | 2.85 |
| 60 | 7.00 | 2.25 |
| 70 | 5.40 | 1.75 |
| 80 | 3.80 | 1.20 |
| 90 | 2.10 | 0.60 |
| 95 | 1.15 | 0.30 |
| 100 | 0.00 | 0.00 |




REFERENCE NO. 787

N.A.C.A.

| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.05 | 1.05 |
| 1¼ | 2.10 | 0.25 |
| 2½ | 2.85 | 0.05 |
| 5 | 4.00 | 0.00 |
| 7½ | 4.95 | 0.10 |
| 10 | 5.75 | 0.30 |
| 15 | 6.85 | 0.70 |
| 20 | 7.60 | 1.05 |
| 30 | 8.25 | 1.80 |
| 40 | 8.05 | 1.86 |
| 50 | 7.35 | 1.90 |
| 60 | 6.40 | 1.70 |
| 70 | 5.10 | 1.35 |
| 80 | 3.50 | 0.95 |
| 90 | 1.90 | 0.50 |
| 95 | 1.00 | 0.25 |
| 100 | 0.00 | 0.00 |






| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.15 | 1.15 |
| 1¼ | 2.35 | 0.25 |
| 2½ | 3.80 | 0.00 |
| 5 | 5.00 | 0.20 |
| 7½ | 6.00 | 0.40 |
| 10 | 6.70 | 0.65 |
| 15 | 7.70 | 1.00 |
| 20 | 8.40 | 1.20 |
| 30 | 9.05 | 1.30 |
| 40 | 8.95 | 1.30 |
| 50 | 8.40 | 1.20 |
| 60 | 7.45 | 1.05 |
| 70 | 6.25 | 0.85 |
| 80 | 4.35 | 0.60 |
| 90 | 3.45 | 0.30 |
| 95 | 2.50 | 0.10 |
| 100 | 0.75 | 0.75 |




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.65 | 0.65 |
| 1¼ | 2.50 | 0.05 |
| 2½ | 3.75 | 0.25 |
| 5 | 5.05 | 0.70 |
| 7½ | 6.25 | 1.10 |
| 10 | 7.05 | 1.50 |
| 15 | 8.15 | 2.20 |
| 20 | 8.85 | 2.55 |
| 30 | 9.30 | 3.85 |
| 40 | 9.15 | 3.90 |
| 50 | 8.55 | 3.65 |
| 60 | 7.55 | 3.20 |
| 70 | 6.25 | 2.50 |
| 80 | 4.50 | 1.70 |
| 90 | 2.40 | 0.60 |
| 95 | 1.20 | 0.40 |
| 100 | 0.00 | 0.00 |




| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.25 | 1.25 |
| 1¼ | 2.75 | 0.30 |
| 2½ | 3.50 | 0.20 |
| 5 | 4.80 | 0.10 |
| 7½ | 6.05 | 0.00 |
| 10 | 6.50 | 0.00 |
| 15 | 7.56 | 0.05 |
| 20 | 8.20 | 0.15 |
| 30 | 8.55 | 0.30 |
| 40 | 8.35 | 0.40 |
| 50 | 7.80 | 0.40 |
| 60 | 6.80 | 0.36 |
| 70 | 5.50 | 0.25 |
| 80 | 4.20 | 0.16 |
| 90 | 2.15 | 0.05 |
| 95 | 1.20 | 0.00 |
| 100 | 0.00 | 0.00 |




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.70 | 0.70 |
| 1¼ | 2.15 | 0.15 |
| 2½ | 2.95 | 0.00 |
| 5 | 4.30 | 0.00 |
| 7½ | 5.30 | 0.10 |
| 10 | 6.10 | 0.35 |
| 15 | 7.30 | 0.80 |
| 20 | 8.10 | 1.20 |
| 30 | 8.70 | 1.65 |
| 40 | 8.55 | 1.90 |
| 50 | 7.85 | 2.00 |
| 60 | 6.90 | 1.85 |
| 70 | 5.50 | 1.55 |
| 80 | 3.85 | 1.05 |
| 90 | 2.15 | 0.50 |
| 95 | 1.10 | 0.25 |
| 100 | 0.00 | 0.00 |

REFERENCE NO.792




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.90 | 0.90 |
| 1¼ | 2.25 | 0.15 |
| 2½ | 3.15 | 0.00 |
| 5 | 4.50 | 0.00 |
| 7½ | 5.50 | 0.20 |
| 10 | 6.30 | 0.45 |
| 15 | 7.60 | 0.90 |
| 20 | 8.40 | 1.25 |
| 30 | 9.20 | 1.70 |
| 40 | 9.10 | 2.20 |
| 50 | 8.35 | 2.00 |
| 60 | 7.30 | 1.85 |
| 70 | 5.80 | 1.50 |
| 80 | 4.10 | 1.10 |
| 90 | 2.20 | 0.55 |
| 95 | 1.15 | 0.30 |
| 100 | 0.00 | 0.00 |

REFERENCE NO.793




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.80 | 0.80 |
| 1¼ | 2.50 | 0.20 |
| 2½ | 3.35 | 0.05 |
| 5 | 4.85 | 0.05 |
| 7½ | 5.90 | 0.15 |
| 10 | 6.80 | 0.40 |
| 15 | 8.10 | 0.85 |
| 20 | 8.95 | 1.20 |
| 30 | 9.60 | 1.70 |
| 40 | 9.40 | 2.00 |
| 50 | 8.65 | 2.10 |
| 60 | 7.50 | 1.95 |
| 70 | 5.95 | 1.60 |
| 80 | 4.20 | 1.10 |
| 90 | 2.25 | 0.60 |
| 95 | 1.15 | 0.35 |
| 100 | 0.00 | 0.00 |

REFERENCE NO.794




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.90 | 0.90 |
| 1¼ | 3.00 | 0.20 |
| 2½ | 3.95 | 0.00 |
| 5 | 5.30 | 0.00 |
| 7½ | 6.20 | 0.10 |
| 10 | 6.80 | 0.15 |
| 15 | 7.70 | 0.35 |
| 20 | 8.30 | 0.60 |
| 30 | 8.65 | 1.15 |
| 40 | 8.30 | 1.45 |
| 50 | 7.55 | 1.55 |
| 60 | 6.65 | 1.45 |
| 70 | 5.45 | 1.15 |
| 80 | 4.00 | 0.80 |
| 90 | 2.21 | 0.32 |
| 95 | 1.15 | 0.15 |
| 100 | 0.00 | 0.00 |

REFERENCE NO.795




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.00 | 0.00 |
| 1¼ | 0.60 | -0.60 |
| 2½ | 0.85 | -0.85 |
| 5 | 1.15 | -1.15 |
| 7½ | 1.45 | -1.45 |
| 10 | 1.60 | -1.60 |
| 15 | 1.90 | -1.90 |
| 20 | 2.15 | -2.15 |
| 30 | 2.50 | -2.50 |
| 40 | 2.50 | -2.50 |
| 50 | 2.35 | -2.35 |
| 60 | 2.05 | -2.05 |
| 70 | 1.60 | -1.60 |
| 80 | 1.15 | -1.15 |
| 90 | 0.65 | -0.65 |
| 95 | 0.30 | -0.30 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 796




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.00 | 0.00 |
| 1¼ | 0.80 | -0.80 |
| 2½ | 0.95 | -0.95 |
| 5 | 1.35 | -1.35 |
| 7½ | 1.65 | -1.65 |
| 10 | 1.90 | -1.90 |
| 15 | 2.35 | -2.35 |
| 20 | 2.55 | -2.55 |
| 30 | 2.80 | -2.80 |
| 40 | 2.85 | -2.85 |
| 50 | 2.75 | -2.75 |
| 60 | 2.25 | -2.25 |
| 70 | 1.95 | -1.95 |
| 80 | 1.40 | -1.40 |
| 90 | 0.80 | -0.80 |
| 95 | 0.65 | -0.65 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 797




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.00 | 0.00 |
| 1¼ | 0.70 | -0.70 |
| 2½ | 1.05 | -1.05 |
| 5 | 1.55 | -1.55 |
| 7½ | 1.90 | -1.90 |
| 10 | 2.20 | -2.20 |
| 15 | 2.65 | -2.65 |
| 20 | 2.90 | -2.90 |
| 30 | 3.05 | -3.05 |
| 40 | 3.20 | -3.20 |
| 50 | 2.95 | -2.95 |
| 60 | 2.55 | -2.55 |
| 70 | 2.10 | -2.10 |
| 80 | 1.50 | -1.50 |
| 90 | 0.90 | -0.90 |
| 95 | 0.45 | -0.45 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 798




| % | UP'R | LW'R |
|---|---|---|
| 0 | 3.00 | 3.00 |
| 1¼ | 4.37 | 1.47 |
| 2½ | 5.42 | 0.92 |
| 5 | 6.63 | 0.42 |
| 7½ | 7.82 | 0.14 |
| 10 | 8.33 | 0.00 |
| 15 | 9.73 | 0.00 |
| 20 | 10.40 | 0.00 |
| 30 | 10.83 | 0.00 |
| 40 | 10.42 | 0.00 |
| 50 | 9.33 | 0.00 |
| 60 | 8.00 | 0.00 |
| 70 | 6.23 | 0.00 |
| 80 | 4.31 | 0.00 |
| 90 | 2.18 | 0.00 |
| 95 | 1.13 | 0.00 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 799




| % | UP'R | LW'R |
|---|---|---|
| 0 | 6.74 | 6.74 |
| 1¼ | 9.10 | 5.10 |
| 2½ | 10.45 | 4.18 |
| 5 | 12.35 | 2.85 |
| 7½ | 13.70 | 1.98 |
| 10 | 14.72 | 1.39 |
| 15 | 16.29 | 0.52 |
| 20 | 17.43 | 0.14 |
| 30 | 18.26 | 0.49 |
| 40 | 17.92 | 1.67 |
| 50 | 16.32 | 2.36 |
| 60 | 14.10 | 2.43 |
| 70 | 11.46 | 2.36 |
| 80 | 7.98 | 1.74 |
| 90 | 4.24 | 1.04 |
| 95 | 2.00 | 0.52 |
| 100 | 0.00 | 0.00 |

REFERENCE NO.800




| % | UP'R | LW'R |
|---|---|---|
| 0 | 8.75 | 8.75 |
| 1¼ | 11.00 | 6.75 |
| 2½ | 12.35 | 5.65 |
| 5 | 14.10 | 3.90 |
| 7½ | 15.38 | 2.68 |
| 10 | 16.85 | 1.80 |
| 15 | 17.40 | 0.70 |
| 20 | 18.06 | 0.21 |
| 30 | 18.06 | 0.14 |
| 40 | 18.81 | 0.69 |
| 50 | 15.21 | 1.67 |
| 60 | 12.85 | 2.22 |
| 70 | 10.28 | 2.29 |
| 80 | 7.29 | 2.01 |
| 90 | 4.03 | 1.25 |
| 95 | 2.08 | 0.65 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 801




| % | UP'R | LW'R |
|---|---|---|
| 0 | 7.00 | 7.00 |
| 1¼ | 11.73 | 5.85 |
| 2½ | 13.28 | 5.14 |
| 5 | 15.51 | 3.95 |
| 7½ | 17.09 | 3.00 |
| 10 | 17.80 | 2.40 |
| 15 | 20.31 | 1.27 |
| 20 | 21.00 | 0.50 |
| 30 | 22.40 | 0.20 |
| 40 | 22.00 | 1.10 |
| 50 | 20.08 | 2.10 |
| 60 | 17.50 | 3.00 |
| 70 | 14.40 | 4.00 |
| 80 | 11.70 | 5.40 |
| 90 | 9.40 | 6.10 |
| 95 | 7.80 | 8.07 |
| 100 | 7.00 | 7.00 |

REFERENCE NO.802




| % | UP'R | LW'R |
|---|---|---|
| 0 | 2.60 | 2.60 |
| 1¼ | 4.54 | 0.56 |
| 2½ | 5.50 | 0.25 |
| 5 | 6.49 | 0.14 |
| 7½ | 7.28 | 0.00 |
| 10 | 7.70 | 0.00 |
| 15 | 8.38 | 0.00 |
| 20 | 8.60 | 0.00 |
| 30 | 9.00 | 0.00 |
| 40 | 8.90 | 0.00 |
| 50 | 8.40 | 0.00 |
| 60 | 7.50 | 0.00 |
| 70 | 6.30 | 0.00 |
| 80 | 4.70 | 0.00 |
| 90 | 3.20 | 0.20 |
| 95 | 2.40 | 0.49 |
| 100 | 1.30 | 1.30 |

REFERENCE NO. 803




| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.18 | 1.18 |
| 1¼ | 3.95 | 0.51 |
| 2½ | 5.08 | 0.14 |
| 5 | 6.77 | 0.00 |
| 7½ | 8.18 | 0.14 |
| 10 | 9.20 | 0.50 |
| 15 | 11.28 | 1.13 |
| 20 | 12.50 | 2.10 |
| 30 | 13.70 | 3.80 |
| 40 | 13.60 | 4.20 |
| 50 | 12.80 | 3.60 |
| 60 | 11.30 | 2.90 |
| 70 | 9.00 | 1.97 |
| 80 | 6.50 | 1.28 |
| 90 | 3.60 | 0.59 |
| 95 | 2.03 | 0.42 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 804




| % | UP'R | LW'R |
|---|---|---|
| 0 | 8.33 | 8.33 |
| 1¼ | 10.52 | 6.00 |
| 2½ | 11.32 | 5.15 |
| 5 | 12.67 | 3.82 |
| 7½ | 13.72 | 2.60 |
| 10 | 14.50 | 1.80 |
| 15 | 15.78 | 0.71 |
| 20 | 16.30 | 0.30 |
| 30 | 16.40 | 0.10 |
| 40 | 15.80 | 0.50 |
| 50 | 14.10 | 1.00 |
| 60 | 12.00 | 1.30 |
| 70 | 9.30 | 1.30 |
| 80 | 6.30 | 1.10 |
| 90 | 3.50 | 0.70 |
| 95 | 1.88 | 0.34 |
| 100 | 0.00 | 0.00 |

Name of section: Eiffel 433a (Chalambel)
Size of model: 38.74" x 6.457"
Wind velocity: 88.58 ft./sec.
Where tested: S.T.Aé. Lab. Date: 1925

REFERENCE NO. 805




| % | UP'R | LW'R |
|---|---|---|
| 0 | 2.20 | 2.20 |
| 1¼ | 4.48 | 0.31 |
| 2½ | 5.64 | 0.00 |
| 5 | 7.39 | 0.14 |
| 7½ | 8.89 | 0.62 |
| 10 | 10.00 | 1.20 |
| 15 | 11.66 | 2.12 |
| 20 | 13.00 | 3.10 |
| 30 | 14.10 | 4.50 |
| 40 | 14.10 | 5.00 |
| 50 | 13.30 | 4.90 |
| 60 | 11.70 | 4.10 |
| 70 | 9.30 | 3.20 |
| 80 | 6.70 | 2.10 |
| 90 | 3.80 | 0.70 |
| 95 | 1.98 | 0.08 |
| 100 | 0.00 | 0.00 |

Name of section: Eiffel 438 (Lachassagne)
Size of model: 23.62" x 3.94"
Wind velocity: 91.86 ft./sec.
Where tested: S.T.Aé. Lab. Date: 1925

REFERENCE NO. 806




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.00 | 0.00 |
| 1¼ | 2.20 | -2.06 |
| 2½ | 3.27 | -2.82 |
| 5 | 5.08 | -3.61 |
| 7½ | 6.40 | -4.01 |
| 10 | 7.33 | -4.37 |
| 15 | 8.74 | -4.51 |
| 20 | 9.82 | -4.17 |
| 30 | 10.86 | -2.54 |
| 40 | 10.86 | -0.65 |
| 50 | 10.16 | 0.42 |
| 60 | 8.74 | 0.85 |
| 70 | 7.14 | 0.99 |
| 80 | 5.30 | 0.99 |
| 90 | 2.96 | 0.65 |
| 95 | 1.69 | 0.42 |
| 100 | 0.00 | 0.00 |

Name of section: St. Cyr 152 (Royer)
Size of model: 38.74" x 6.46"
Wind velocity: 131.2 ft./sec.
Where tested: S.T.Aé. Lab. Date: 1925

REFERENCE NO. 807




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.00 | -0.00 |
| 1¼ | 3.38 | -2.81 |
| 2½ | 4.75 | -3.83 |
| 5 | 6.55 | -4.78 |
| 7½ | 8.02 | -5.37 |
| 10 | 8.90 | -5.70 |
| 15 | 10.55 | -6.19 |
| 20 | 11.70 | -6.00 |
| 30 | 12.80 | -4.70 |
| 40 | 12.70 | -3.40 |
| 50 | 11.80 | -2.00 |
| 60 | 10.50 | -0.80 |
| 70 | 8.30 | -0.10 |
| 80 | 6.00 | 0.00 |
| 90 | 3.10 | 0.00 |
| 95 | 1.69 | 0.00 |
| 100 | 0.00 | 0.00 |

Name of section: St. Cyr 153 (Royer)
Size of model: 38.74" x 6.46"
Wind velocity: 131.2 ft./sec.
Where tested: S.T.Aé. Lab. Date: 1925

REFERENCE NO. 808




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.00 | -0.00 |
| 1¼ | 3.81 | -2.68 |
| 2½ | 5.22 | -3.39 |
| 5 | 7.39 | -4.09 |
| 7½ | 9.05 | -4.46 |
| 10 | 11.00 | -3.80 |
| 15 | 12.69 | -4.09 |
| 20 | 14.40 | -3.00 |
| 30 | 16.30 | -1.40 |
| 40 | 16.80 | 0.10 |
| 50 | 16.00 | 1.80 |
| 60 | 14.40 | 3.00 |
| 70 | 11.70 | 3.20 |
| 80 | 8.30 | 3.00 |
| 90 | 4.50 | 1.80 |
| 95 | 2.60 | 1.07 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 809




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.00 | 0.00 |
| 1¼ | 2.54 | -1.95 |
| 2½ | 3.81 | -2.34 |
| 5 | 5.79 | -2.60 |
| 7½ | 7.34 | -2.48 |
| 10 | 8.76 | -1.98 |
| 15 | 11.02 | -1.13 |
| 20 | 12.94 | 0.00 |
| 30 | 15.42 | 2.54 |
| 40 | 15.71 | 4.32 |
| 50 | 13.42 | 4.80 |
| 60 | 10.88 | 3.90 |
| 70 | 8.33 | 2.82 |
| 80 | 5.65 | 1.84 |
| 90 | 2.97 | 0.85 |
| 95 | 1.64 | 0.45 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 810




| % | UP'R | LW'R |
|---|---|---|
| 0 | 6.50 | 6.50 |
| 1¼ | 9.59 | 4.01 |
| 2½ | 10.49 | 3.24 |
| 5 | 11.90 | 1.98 |
| 7½ | 12.92 | 1.22 |
| 10 | 13.50 | 0.70 |
| 15 | 14.75 | 0.14 |
| 20 | 15.40 | 0.00 |
| 30 | 16.30 | 1.00 |
| 40 | 16.00 | 2.80 |
| 50 | 15.00 | 2.80 |
| 60 | 13.30 | 2.80 |
| 70 | 11.00 | 2.50 |
| 80 | 8.30 | 2.22 |
| 90 | 5.60 | 1.30 |
| 95 | 4.17 | 0.79 |
| 100 | 2.50 | 0.00 |

REFERENCE NO. 811




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.00 | -0.00 |
| 1¼ | 1.89 | -1.89 |
| 2½ | 2.54 | -2.54 |
| 5 | 3.33 | -3.33 |
| 7½ | 3.87 | -3.87 |
| 10 | 4.24 | -4.24 |
| 15 | 4.66 | -4.66 |
| 20 | 4.80 | -4.80 |
| 30 | 4.80 | -4.80 |
| 40 | 4.66 | -4.66 |
| 50 | 4.21 | -4.21 |
| 60 | 3.53 | -3.53 |
| 70 | 2.82 | -2.82 |
| 80 | 2.03 | -2.03 |
| 90 | 1.13 | -1.13 |
| 9 | 0.71 | -0.71 |
| 100 | 0.00 | -0.00 |

REFERENCE NO.813




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.00 | -0.00 |
| 1¼ | 3.39 | -3.39 |
| 2½ | 4.85 | -4.85 |
| 5 | 6.83 | -6.83 |
| 7½ | 7.90 | -7.90 |
| 10 | 9.03 | -9.03 |
| 15 | 10.38 | -10.38 |
| 20 | 10.88 | -10.88 |
| 30 | 11.28 | -11.28 |
| 40 | 10.72 | -10.72 |
| 50 | 9.65 | -9.65 |
| 60 | 8.32 | -8.32 |
| 70 | 6.49 | -6.49 |
| 80 | 4.51 | -4.51 |
| 90 | 2.40 | -2.40 |
| 95 | 1.13 | -1.13 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 813




| % | UP'R | LW'R |
|---|---|---|
| 0 | 8.11 | 8.11 |
| 1¼ | 10.80 | 5.60 |
| 2½ | 12.00 | 4.30 |
| 5 | 13.50 | 2.90 |
| 7½ | 14.37 | 2.15 |
| 10 | 14.90 | 1.55 |
| 15 | 15.63 | 0.85 |
| 20 | 16.00 | 0.30 |
| 30 | 16.00 | 0.00 |
| 40 | 15.20 | 0.00 |
| 50 | 14.20 | 0.00 |
| 60 | 12.42 | 0.00 |
| 70 | 10.05 | 0.00 |
| 80 | 7.15 | 0.00 |
| 90 | 3.65 | 0.00 |
| 95 | 1.85 | 0.00 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 814




| % | UP'R | LW'R |
|---|---|---|
| 0 | 8.28 | 6.28 |
| 1¼ | 9.00 | 3.80 |
| 2½ | 10.20 | 2.80 |
| 5 | 11.80 | 1.50 |
| 7½ | 12.85 | 0.85 |
| 10 | 13.85 | 0.50 |
| 15 | 14.80 | 0.18 |
| 20 | 15.60 | 0.03 |
| 30 | 16.20 | 0.55 |
| 40 | 16.01 | 1.12 |
| 50 | 15.10 | 1.35 |
| 60 | 13.25 | 1.40 |
| 70 | 10.88 | 1.30 |
| 80 | 7.80 | 1.00 |
| 90 | 4.05 | 0.50 |
| 95 | 2.05 | 0.29 |
| 100 | 0.00 | 0.00 |

REFERENCE NO.815




| % | UP'R | LW'R |
|---|---|---|
| 0 | 4.59 | 4.59 |
| 1¼ | 6.80 | 2.80 |
| 2½ | 7.95 | 1.75 |
| 5 | 9.30 | 0.90 |
| 7½ | 10.12 | 0.40 |
| 10 | 10.70 | 0.15 |
| 15 | 11.58 | 0.05 |
| 20 | 12.20 | 0.20 |
| 30 | 12.57 | 0.78 |
| 40 | 12.49 | 1.30 |
| 50 | 11.75 | 1.50 |
| 60 | 10.40 | 1.50 |
| 70 | 8.40 | 1.40 |
| 80 | 6.02 | 1.00 |
| 90 | 3.00 | 0.60 |
| 95 | 1.50 | 0.40 |
| 100 | 0.00 | 0.00 |

REFERENCE NO.816




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.00 | 0.00 |
| 1¼ | 4.00 | -1.50 |
| 2½ | 5.60 | -2.10 |
| 5 | 7.85 | -2.80 |
| 7½ | 8.90 | -3.20 |
| 10 | 9.80 | -3.40 |
| 15 | 10.78 | -3.70 |
| 20 | 11.48 | -3.90 |
| 30 | 11.65 | -3.95 |
| 40 | 11.35 | -3.70 |
| 50 | 10.45 | -3.35 |
| 60 | 9.10 | -2.90 |
| 70 | 7.35 | -2.30 |
| 80 | 5.15 | -1.60 |
| 90 | 2.50 | -0.85 |
| 95 | 1.25 | -0.43 |
| 100 | 0.00 | -0.00 |

REFERENCE NO.817




| % | UP'R | LW'R |
|---|---|---|
| 0 | 4.39 | 4.39 |
| 1¼ | 8.30 | 2.50 |
| 2½ | 9.75 | 1.80 |
| 5 | 12.00 | 1.10 |
| 7½ | 13.28 | 0.78 |
| 10 | 14.18 | 0.55 |
| 15 | 15.20 | 0.20 |
| 20 | 15.72 | 0.05 |
| 30 | 16.00 | 0.00 |
| 40 | 15.45 | 0.00 |
| 50 | 14.10 | 0.00 |
| 60 | 12.10 | 0.00 |
| 70 | 9.80 | 0.00 |
| 80 | 6.75 | 0.00 |
| 90 | 3.45 | 0.00 |
| 95 | 1.75 | 0.00 |
| 100 | 0.00 | 0.00 |

REFERENCE NO.818




| % | UP'R | LW'R |
|---|---|---|
| 0 | 2.77 | 2.77 |
| 1¼ | 6.50 | 1.50 |
| 2½ | 8.20 | 0.75 |
| 5 | 10.80 | 0.30 |
| 7½ | 12.10 | 0.10 |
| 10 | 13.15 | 0.05 |
| 15 | 14.80 | 0.03 |
| 20 | 15.75 | 0.30 |
| 30 | 16.65 | 0.75 |
| 40 | 16.88 | 1.30 |
| 50 | 15.66 | 1.38 |
| 60 | 13.85 | 1.75 |
| 70 | 11.38 | 1.50 |
| 80 | 8.05 | 1.20 |
| 90 | 4.10 | 0.60 |
| 95 | 2.05 | 0.28 |
| 100 | 0.00 | 0.00 |

REFERENCE NO.819




| % | UP'R | LW'R |
|---|---|---|
| 0 | 3.51 | 3.51 |
| 1¼ | 7.75 | 1.53 |
| 2½ | 9.45 | 1.00 |
| 5 | 11.75 | 0.35 |
| 7½ | 13.22 | 0.15 |
| 10 | 14.29 | 0.13 |
| 15 | 15.73 | 0.25 |
| 20 | 16.50 | 0.53 |
| 30 | 17.29 | 1.00 |
| 40 | 17.08 | 1.30 |
| 50 | 16.03 | 1.40 |
| 60 | 14.09 | 1.27 |
| 70 | 11.32 | 1.18 |
| 80 | 8.15 | 0.78 |
| 90 | 4.18 | 0.40 |
| 95 | 2.08 | 0.18 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 820




| % | UP'R | LW'R |
|---|---|---|
| 0 | 12.50 | 12.50 |
| 1¼ | 16.40 | 8.65 |
| 2½ | 18.50 | 7.00 |
| 5 | 21.00 | 5.13 |
| 7½ | 22.50 | 3.63 |
| 10 | 23 75 | 2.83 |
| 15 | 25.28 | 1.37 |
| 20 | 28.13 | 0.50 |
| 30 | 26.25 | 0.00 |
| 40 | 25.25 | 0.83 |
| 50 | 22.50 | 1.38 |
| 60 | 19.00 | 2.00 |
| 70 | 15.00 | 2.63 |
| 80 | 10.38 | 2.78 |
| 90 | 6.50 | 2.00 |
| 95 | 3.00 | 1.28 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 821




| % | UP'R | LW'R |
|---|---|---|
| 0 | 4.50 | 4.50 |
| 1¼ | 7.10 | 2.50 |
| 2½ | 8.13 | 1.75 |
| 5 | 9.83 | 1.00 |
| 7½ | 10.63 | 0.83 |
| 10 | 11.50 | 0.38 |
| 15 | 12.70 | 0.20 |
| 20 | 13.38 | 0.13 |
| 30 | 13.88 | 0.63 |
| 40 | 13.88 | 1.38 |
| 50 | 12.83 | 2.00 |
| 60 | 11.00 | 2.50 |
| 70 | 9.00 | 2.75 |
| 80 | 6.25 | 2.26 |
| 90 | 3.25 | 1.50 |
| 95 | 1.75 | 0.75 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 822




| % | UP'R | LW'R |
|---|---|---|
| 0 | 2.92 | 2.92 |
| 1¼ | 4.52 | 1.40 |
| 2½ | 5.55 | 0.75 |
| 5 | 7.50 | 0.25 |
| 7½ | 8.72 | 0.08 |
| 10 | 9.62 | 0.00 |
| 15 | 10.81 | 0.00 |
| 20 | 11.48 | 0.00 |
| 30 | 11.73 | 0.00 |
| 40 | 11.15 | 0.00 |
| 50 | 10.25 | 0.00 |
| 60 | 8.82 | 0.00 |
| 70 | 7.15 | 0.00 |
| 80 | 5.18 | 0.00 |
| 90 | 3.01 | 0.09 |
| 95 | 1.01 | 0.20 |
| 100 | 0.30 | 0.35 |

REFERENCE NO. 823




| % | UP'R | LW'R |
|---|---|---|
| 0 | 6.75 | 6.75 |
| 1¼ | 9.70 | 4.85 |
| 2½ | 10.88 | 3.88 |
| 5 | 12.50 | 2.83 |
| 7½ | 13.75 | 1.63 |
| 10 | 14.75 | 1.13 |
| 15 | 16.18 | 0.40 |
| 20 | 17.00 | 0.25 |
| 30 | 17.50 | 0.25 |
| 40 | 16.88 | 0.75 |
| 50 | 15.38 | 1.63 |
| 60 | 13.25 | 2.50 |
| 70 | 10.38 | 2.86 |
| 80 | 7.00 | 2.50 |
| 90 | 3.63 | 1.50 |
| 95 | 1.75 | 0.75 |
| 100 | 0.00 | 0.00 |

REFERENCE NO. 824

| % | UP'R | LW'R |
|---|---|---|
| 0 | 2.50 | 2.50 |
| 1¼ | 4.55 | 1.26 |
| 2½ | 5.63 | 0.75 |
| 5 | 7.25 | 0.25 |
| 7½ | 8.38 | 0.25 |
| 10 | 9.50 | 0.38 |
| 15 | 11.22 | 0.80 |
| 20 | 12.50 | 1.13 |
| 30 | 13.88 | 1.50 |
| 40 | 13.75 | 1.63 |
| 50 | 12.88 | 1.75 |
| 60 | 11.38 | 1.63 |
| 70 | 9.50 | 1.38 |
| 80 | 7.00 | 1.00 |
| 90 | 3.88 | 0.63 |
| 95 | 2.00 | 0.38 |
| 100 | 0.00 | 0.00 |




REFERENCE NO. 825

| % | UP'R | LW'R |
|---|---|---|
| 0 | 2.50 | 2.50 |
| 1¼ | 3.75 | 2.05 |
| 2½ | 4.50 | 1.75 |
| 5 | 5.50 | 1.30 |
| 7½ | 6.38 | 0.88 |
| 10 | 6.80 | 0.60 |
| 15 | 8.15 | 0.39 |
| 20 | 9.10 | 0.20 |
| 30 | 10.00 | 0.00 |
| 40 | 9.80 | 0.00 |
| 50 | 8.80 | 0.00 |
| 60 | 7.30 | 0.00 |
| 70 | 5.50 | 0.00 |
| 80 | 3.90 | 0.00 |
| 90 | 2.10 | 0.00 |
| 95 | 1.00 | 0.00 |
| 100 | 0.00 | 0.00 |




REFERENCE NO. 826

| % | UP'R | LW'R |
|---|---|---|
| 0 | 2.13 | 2.13 |
| 1¼ | 3.80 | 0.98 |
| 2½ | 4.53 | 0.53 |
| 5 | 5.53 | 0.27 |
| 7½ | 6.40 | 0.14 |
| 10 | 7.15 | 0.00 |
| 15 | 8.10 | 0.00 |
| 20 | 8.53 | 0.00 |
| 30 | 8.68 | 0.00 |
| 40 | 8.27 | 0.00 |
| 50 | 7.80 | 0.00 |
| 60 | 6.53 | 0.00 |
| 70 | 5.20 | 0.00 |
| 80 | 3.60 | 0.00 |
| 90 | 1.80 | 0.00 |
| 95 | 0.95 | 0.00 |
| 100 | 0.00 | 0.00 |




REFERENCE NO. 827

| % | UP'R | LW'R |
|---|---|---|
| 0 | 2.67 | 2.67 |
| 1¼ | 4.70 | 1.20 |
| 2½ | 5.67 | 0.66 |
| 5 | 6.92 | 0.34 |
| 7½ | 8.00 | 0.17 |
| 10 | 8.75 | 0.00 |
| 15 | 9.95 | 0.00 |
| 20 | 10.66 | 0.00 |
| 30 | 10.82 | 0.00 |
| 40 | 10.33 | 0.00 |
| 50 | 9.50 | 0.00 |
| 60 | 8.16 | 0.00 |
| 70 | 6.50 | 0.00 |
| 80 | 4.50 | 0.00 |
| 90 | 2.75 | 0.00 |
| 95 | 1.17 | 0.00 |
| 100 | 0.00 | 0.00 |



REFERENCE NO. 828




| % | UP'R | LW'R |
|---|---|---|
| 0 | 3.20 | 3.20 |
| 1¼ | 5.75 | 1.92 |
| 2½ | 6.80 | 0.79 |
| 5 | 8.30 | 0.36 |
| 7½ | 9.60 | 0.21 |
| 10 | 10.50 | 0.00 |
| 15 | 12.05 | 0.00 |
| 20 | 12.79 | 0.00 |
| 30 | 12.99 | 0.00 |
| 40 | 12.40 | 0.00 |
| 50 | 11.40 | 0.00 |
| 60 | 9.79 | 0.00 |
| 70 | 7.80 | 0.00 |
| 80 | 5.40 | 0.00 |
| 90 | 2.70 | 0.00 |
| 95 | 1.40 | 0.00 |
| 100 | 0.00 | 0.00 |

Name of section: Rhode St. Genese 33
Size of model: 39.37" x 7.874"
Wind velocity: 98.4 ft./sec.
Where tested: Rhode St. Genese Date: 1927

REFERENCE NO. 829




| % | UP'R | LW'R |
|---|---|---|
| 0 | 3.73 | 3.73 |
| 1¼ | 6.65 | 1.65 |
| 2½ | 7.93 | 0.93 |
| 5 | 9.68 | 0.47 |
| 7½ | 11.20 | 0.24 |
| 10 | 12.25 | 0.00 |
| 15 | 13.88 | 0.00 |
| 20 | 14.93 | 0.00 |
| 30 | 15.15 | 0.00 |
| 40 | 14.46 | 0.00 |
| 50 | 13.30 | 0.00 |
| 60 | 11.43 | 0.00 |
| 70 | 9.10 | 0.00 |
| 80 | 6.30 | 0.00 |
| 90 | 3.15 | 0.00 |
| 95 | 1.63 | 0.00 |
| 100 | 0.00 | 0.00 |

Name of section: Rhode St. Genese 35
Size of model: 39.37" x 7.874"
Wind velocity: 98.4 ft./sec.
Where tested: Rhode St. Genese Date: 1927

REFERENCE NO. 830




| % | UP'R | LW'R |
|---|---|---|
| 0 | 4.27 | 4.27 |
| 1¼ | 7.70 | 1.80 |
| 2½ | 9.07 | 1.08 |
| 5 | 11.07 | 0.54 |
| 7½ | 12.79 | 0.27 |
| 10 | 13.94 | 0.00 |
| 15 | 15.85 | 0.00 |
| 20 | 17.08 | 0.00 |
| 30 | 17.31 | 0.00 |
| 40 | 16.53 | 0.00 |
| 50 | 15.19 | 0.00 |
| 60 | 13.06 | 0.00 |
| 70 | 10.40 | 0.00 |
| 80 | 7.20 | 0.00 |
| 90 | 3.80 | 0.00 |
| 95 | 1.87 | 0.00 |
| 100 | 0.00 | 0.00 |

Name of section: Rhode St. Genese 37
Size of model: 39.37" x 7.874"
Wind velocity: 98.4 ft./sec.
Where tested: Rhode St. Genese Date: 1927

REFERENCE NO. 831




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.45 | 0.45 |
| 1¼ | 1.65 | 0.08 |
| 2½ | 2.47 | 0.00 |
| 5 | 3.71 | 0.17 |
| 7½ | 4.80 | 0.50 |
| 10 | 5.58 | 1.14 |
| 15 | 6.90 | 2.20 |
| 20 | 7.13 | 3.10 |
| 30 | 9.57 | 4.25 |
| 40 | 9.63 | 4.45 |
| 50 | 8.38 | 4.10 |
| 60 | 7.46 | 3.34 |
| 70 | 6.23 | 2.47 |
| 80 | 4.85 | 1.80 |
| 90 | 2.72 | 0.80 |
| 95 | 1.75 | 0.40 |
| 100 | 0.45 | 0.00 |

Name of section: I. S. A. 334
Size of model: 31.496" x 5.249"
Wind velocity: 49.2 ft./sec.
Where tested: I. S. A. Date: 1917

REFERENCE NO. 832

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.71 | 0.71 |
| 1¼ | 1.68 | 0.15 |
| 2½ | 2.23 | 0.05 |
| 5 | 3.07 | 0.06 |
| 7½ | 4.00 | 0.30 |
| 10 | 4.55 | 0.60 |
| 15 | 5.42 | 1.35 |
| 20 | 6.00 | 1.80 |
| 30 | 6.30 | 2.45 |
| 40 | 6.00 | 2.41 |
| 50 | 5.37 | 2.02 |
| 60 | 4.50 | 1.67 |
| 70 | 3.47 | 1.05 |
| 80 | 2.45 | 0.65 |
| 90 | 1.32 | 0.20 |
| 95 | 0.82 | 0.00 |
| 100 | 0.21 | 0.00 |




REFERENCE NO. 833

| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.27 | 1.27 |
| 1¼ | 2.20 | 0.79 |
| 2½ | 2.80 | 0.60 |
| 5 | 3.68 | 0.15 |
| 7½ | 4.37 | 0.00 |
| 10 | 4.77 | 0.00 |
| 15 | 5.48 | 0.15 |
| 20 | 6.11 | 0.50 |
| 30 | 6.33 | 0.87 |
| 40 | 5.97 | 1.21 |
| 50 | 5.26 | 1.46 |
| 60 | 4.03 | 1.50 |
| 70 | 2.87 | 1.32 |
| 80 | 1.89 | 0.89 |
| 90 | 1.00 | 0.37 |
| 95 | 0.65 | 0.10 |
| 100 | 0.26 | 0.00 |




REFERENCE NO. 834

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.95 | 0.95 |
| 1¼ | 2.35 | 0.18 |
| 2½ | 3.19 | 0.00 |
| 5 | 4.50 | 0.00 |
| 7½ | 5.80 | 0.05 |
| 10 | 6.95 | 0.18 |
| 15 | 8.91 | 0.30 |
| 20 | 10.62 | 0.45 |
| 30 | 12.42 | 0.72 |
| 40 | 12.20 | 0.94 |
| 50 | 10.80 | 1.00 |
| 60 | 9.25 | 0.81 |
| 70 | 7.50 | 0.67 |
| 80 | 5.64 | 0.43 |
| 90 | 3.70 | 0.18 |
| 95 | 2.82 | 0.00 |
| 100 | 0.85 | 0.85 |




REFERENCE NO. 835

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.82 | 0.82 |
| 1¼ | 2.25 | 0.18 |
| 2½ | 2.90 | 0.02 |
| 5 | 4.02 | 0.00 |
| 7½ | 5.20 | 0.15 |
| 10 | 6.00 | 0.17 |
| 15 | 7.59 | 0.28 |
| 20 | 8.82 | 0.43 |
| 30 | 10.19 | 0.67 |
| 40 | 10.19 | 0.86 |
| 50 | 9.39 | 0.93 |
| 60 | 8.22 | 0.82 |
| 70 | 6.81 | 0.70 |
| 80 | 5.00 | 0.48 |
| 90 | 3.25 | 0.25 |
| 95 | 2.35 | 0.10 |
| 100 | 0.70 | 0.70 |



REFERENCE NO. 836

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.82 | 0.82 |
| 1¼ | 2.10 | 0.15 |
| 2½ | 2.65 | 0.00 |
| 5 | 3.31 | 0.12 |
| 7½ | 4.00 | 0.20 |
| 10 | 4.73 | 0.25 |
| 15 | 5.88 | 0.40 |
| 20 | 6.05 | 0.57 |
| 30 | 8.24 | 0.80 |
| 40 | 8.38 | 1.00 |
| 50 | 7.89 | 1.08 |
| 60 | 7.12 | 0.94 |
| 70 | 6.06 | 0.74 |
| 80 | 4.72 | 0.50 |
| 90 | 3.15 | 0.24 |
| 95 | 2.40 | 0.02 |
| 100 | 0.70 | 0.70 |




REFERENCE NO. 837

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.00 | 0.00 |
| 1¼ | 1.15 | 0.00 |
| 2½ | 2.00 | 0.00 |
| 5 | 2.82 | 0.00 |
| 7½ | 3.50 | 0.00 |
| 10 | 3.92 | 0.00 |
| 15 | 4.50 | 0.00 |
| 20 | 4.87 | 0.00 |
| 30 | 4.97 | 0.00 |
| 40 | 4.75 | 0.00 |
| 50 | 4.37 | 0.00 |
| 60 | 3.82 | 0.00 |
| 70 | 3.07 | 0.00 |
| 80 | 2.20 | 0.00 |
| 90 | 1.19 | 0.00 |
| 95 | 0.70 | 0.00 |
| 100 | 0.00 | 0.00 |




REFERENCE NO. 838

| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.12 | 1.12 |
| 1¼ | 2.05 | 0.45 |
| 2½ | 2.50 | 0.17 |
| 5 | 3.20 | 0.00 |
| 7½ | 3.95 | 0.05 |
| 10 | 4.37 | 0.20 |
| 15 | 5.10 | 0.65 |
| 20 | 5.57 | 1.05 |
| 30 | 5.90 | 1.32 |
| 40 | 5.80 | 1.32 |
| 50 | 5.42 | 1.17 |
| 60 | 4.80 | 0.92 |
| 70 | 4.05 | 0.65 |
| 80 | 3.07 | 0.32 |
| 90 | 1.80 | 0.00 |
| 95 | 1.18 | 0.00 |
| 100 | 0.50 | 0.15 |




REFERENCE NO. 839

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.95 | 0.95 |
| 1¼ | 2.10 | 0.40 |
| 2½ | 2.70 | 0.17 |
| 5 | 3.42 | 0.00 |
| 7½ | 4.10 | 0.00 |
| 10 | 4.60 | 0.00 |
| 15 | 5.38 | 0.08 |
| 20 | 5.90 | 0.32 |
| 30 | 6.32 | 0.65 |
| 40 | 6.02 | 0.77 |
| 50 | 5.37 | 0.85 |
| 60 | 4.55 | 0.80 |
| 70 | 3.72 | 0.67 |
| 80 | 2.85 | 0.42 |
| 90 | 1.87 | 0.12 |
| 95 | 0.90 | 0.00 |
| 100 | 0.42 | 0.15 |



REFERENCE NO. 840

| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.90 | 1.90 |
| 1¼ | 3.15 | 0.90 |
| 2½ | 3.90 | 0.50 |
| 5 | 5.12 | 0.20 |
| 7½ | 5.90 | 0.00 |
| 10 | 6.70 | 0.00 |
| 15 | 7.75 | 0.25 |
| 20 | 8.37 | 0.67 |
| 30 | 8.65 | 1.35 |
| 40 | 8.12 | 1.95 |
| 50 | 7.12 | 2.38 |
| 60 | 5.70 | 2.38 |
| 70 | 4.20 | 2.05 |
| 80 | 2.78 | 1.40 |
| 90 | 1.45 | 0.63 |
| 95 | 1.00 | 0.45 |
| 100 | 0.30 | 0.00 |




REFERENCE NO. 841

| % | UP'R | LW'R |
|---|---|---|
| 0 | 5.00 | 5.00 |
| 1¼ | 6.80 | 3.70 |
| 2½ | 7.90 | 2.90 |
| 5 | 9.87 | 1.70 |
| 7½ | 11.10 | 1.00 |
| 10 | 12.32 | 0.58 |
| 15 | 14.00 | 0.21 |
| 20 | 15.15 | 0.27 |
| 30 | 16.20 | 1.42 |
| 40 | 15.75 | 2.45 |
| 50 | 14.12 | 3.10 |
| 60 | 11.80 | 3.37 |
| 70 | 8.45 | 3.10 |
| 80 | 5.27 | 2.20 |
| 90 | 2.45 | 0.95 |
| 95 | 1.40 | 0.50 |
| 100 | 0.43 | 0.00 |




REFERENCE NO. 842

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.35 | 0.35 |
| 1¼ | 1.95 | 0.00 |
| 2½ | 3.10 | 0.00 |
| 5 | 5.02 | 0.00 |
| 7½ | 6.35 | 0.00 |
| 10 | 7.25 | -0.25 |
| 15 | 8.33 | -0.33 |
| 20 | 9.07 | -0.44 |
| 30 | 9.42 | -0.55 |
| 40 | 9.02 | -0.70 |
| 50 | 8.30 | -0.80 |
| 60 | 7.30 | -0.70 |
| 70 | 6.17 | -0.62 |
| 80 | 4.30 | -0.45 |
| 90 | 2.44 | -0.31 |
| 95 | 1.70 | 0.00 |
| 100 | 0.52 | 0.00 |




REFERENCE NO. 843

| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.25 | 0.25 |
| 1¼ | 1.75 | 0.00 |
| 2½ | 2.60 | 0.00 |
| 5 | 3.72 | 0.00 |
| 7½ | 4.60 | 0.00 |
| 10 | 5.05 | 0.07 |
| 15 | 5.50 | 0.15 |
| 20 | 5.75 | 0.19 |
| 30 | 5.81 | 0.30 |
| 40 | 5.82 | 0.32 |
| 50 | 5.12 | 0.31 |
| 60 | 4.62 | 0.30 |
| 70 | 3.95 | 0.23 |
| 80 | 3.15 | 0.10 |
| 90 | 2.10 | 0.00 |
| 95 | 1.40 | 0.00 |
| 100 | 0.30 | 0.00 |



REFERENCE NO. 84




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.75 | 0.75 |
| 1¼ | 1.65 | 0.25 |
| 2½ | 2.10 | 0.17 |
| 5 | 3.12 | 0.07 |
| 7½ | 3.70 | 0.25 |
| 10 | 4.45 | 0.65 |
| 15 | 5.25 | 1.22 |
| 20 | 5.87 | 1.68 |
| 30 | 6.32 | 2.06 |
| 40 | 6.07 | 2.04 |
| 50 | 5.43 | 1.75 |
| 60 | 4.60 | 1.37 |
| 70 | 3.50 | 0.97 |
| 80 | 2.45 | 0.80 |
| 90 | 1.32 | 0.27 |
| 95 | 1.00 | 0.20 |
| 100 | 0.25 | 0.00 |

Name of section: I. S. A. 801
Size of model: 31.89" x 5.315"
Wind velocity: 65.6 ft./sec.
Where tested: I. S. A. Date: 1920

REFERENCE NO.845




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.75 | 0.75 |
| 1¼ | 2.15 | 0.30 |
| 2½ | 2.70 | 0.20 |
| 5 | 3.56 | 0.00 |
| 7½ | 4.40 | 0.40 |
| 10 | 4.93 | 0.89 |
| 15 | 5.72 | 1.65 |
| 20 | 6.25 | 1.92 |
| 30 | 6.55 | 2.12 |
| 40 | 6.30 | 1.85 |
| 50 | 5.70 | 1.35 |
| 60 | 4.92 | 0.87 |
| 70 | 3.82 | 0.44 |
| 80 | 2.70 | 0.17 |
| 90 | 1.50 | 0.04 |
| 95 | 1.00 | 0.00 |
| 100 | 0.35 | 0.00 |

Name of section: I. S. A. 803
Size of model: 31.50" x 5.249"
Wind velocity: 65.6 ft./sec.
Where tested: I. S. A. Date: 1920

REFERENCE NO.846




| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.12 | 1.12 |
| 1¼ | 2.30 | 0.45 |
| 2½ | 2.95 | 0.20 |
| 5 | 3.97 | 0.00 |
| 7½ | 4.85 | 0.20 |
| 10 | 5.37 | 0.50 |
| 15 | 6.10 | 1.22 |
| 20 | 6.47 | 1.85 |
| 30 | 6.80 | 2.12 |
| 40 | 6.62 | 1.87 |
| 50 | 6.12 | 1.37 |
| 60 | 5.32 | 0.82 |
| 70 | 4.25 | 0.42 |
| 80 | 3.00 | 0.19 |
| 90 | 1.75 | 0.07 |
| 95 | 1.20 | 0.00 |
| 100 | 0.40 | 0.00 |

Name of section: I. S. A. 804
Size of model: 27.56" x 4.593"
Wind velocity: 65.7 ft./sec.
Where tested: I. S. A. Date: 1920

REFERENCE NO.847




| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.00 | 1.00 |
| 1¼ | 2.00 | 0.50 |
| 2½ | 2.50 | 0.20 |
| 5 | 3.34 | 0.00 |
| 7½ | 4.00 | 0.15 |
| 10 | 4.43 | 0.50 |
| 15 | 5.00 | 1.40 |
| 20 | 5.30 | 1.65 |
| 30 | 5.37 | 1.85 |
| 40 | 5.18 | 1.47 |
| 50 | 4.65 | 1.05 |
| 60 | 4.07 | 0.57 |
| 70 | 3.32 | 0.22 |
| 80 | 2.40 | 0.10 |
| 90 | 1.32 | 0.00 |
| 95 | 1.00 | 0.00 |
| 100 | 0.27 | 0.00 |

Name of section: I. S. A. 805
Size of model: 31.50" x 5.249"
Wind velocity: 65.6 ft./sec.
Where tested: I. S. A. Date: 1920

REFERENCE NO.848




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.87 | 0.87 |
| 1¼ | 1.52 | 0.40 |
| 2½ | 2.00 | 0.18 |
| 5 | 2.87 | 0.00 |
| 7½ | 3.50 | 0.15 |
| 10 | 4.05 | 0.35 |
| 15 | 4.80 | 0.95 |
| 20 | 5.25 | 1.37 |
| 30 | 5.62 | 1.87 |
| 40 | 5.53 | 1.68 |
| 50 | 5.12 | 1.35 |
| 60 | 4.42 | 0.94 |
| 70 | 3.57 | 0.62 |
| 80 | 2.67 | 0.35 |
| 90 | 1.82 | 0.25 |
| 95 | 1.15 | 0.10 |
| 100 | 0.30 | 0.00 |

REFERENCE NO.849




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.50 | 0.50 |
| 1¼ | 1.75 | 0.12 |
| 2½ | 2.40 | 0.10 |
| 5 | 3.27 | 0.00 |
| 7½ | 4.10 | 0.10 |
| 10 | 4.82 | 0.25 |
| 15 | 5.40 | 0.75 |
| 20 | 5.83 | 1.31 |
| 30 | 6.12 | 1.70 |
| 40 | 6.00 | 1.87 |
| 50 | 5.57 | 1.30 |
| 60 | 4.87 | 0.67 |
| 70 | 3.92 | 0.45 |
| 80 | 2.74 | 0.20 |
| 90 | 1.50 | 0.08 |
| 95 | 1.06 | 0.00 |
| 100 | 0.25 | 0.00 |

REFERENCE NO.850




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.70 | 0.70 |
| 1¼ | 2.15 | 0.18 |
| 2½ | 2.80 | 0.20 |
| 5 | 3.69 | 0.50 |
| 7½ | 4.40 | 0.80 |
| 10 | 4.82 | 1.10 |
| 15 | 5.55 | 1.50 |
| 20 | 5.95 | 1.82 |
| 30 | 6.18 | 1.95 |
| 40 | 5.88 | 1.75 |
| 50 | 5.18 | 1.25 |
| 60 | 4.23 | 0.77 |
| 70 | 3.15 | 0.29 |
| 80 | 2.27 | 0.00 |
| 90 | 1.45 | 0.10 |
| 95 | 1.00 | 0.20 |
| 100 | 0.50 | 0.40 |

REFERENCE NO.851




| % | UP'R | LW'R |
|---|---|---|
| 0 | 4.50 | 4.50 |
| 1¼ | 5.80 | 2.85 |
| 2½ | 6.30 | 2.10 |
| 5 | 6.80 | 1.10 |
| 7½ | 7.10 | 0.65 |
| 10 | 7.35 | 0.30 |
| 15 | 7.50 | 0.05 |
| 20 | 7.50 | 0.00 |
| 30 | 7.30 | 0.55 |
| 40 | 6.75 | 1.20 |
| 50 | 5.90 | 1.60 |
| 60 | 4.95 | 1.70 |
| 70 | 4.00 | 1.60 |
| 80 | 2.85 | 1.15 |
| 90 | 1.68 | 0.60 |
| 95 | 1.20 | 0.40 |
| 100 | 0.40 | 0.00 |

REFERENCE NO. 852




| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.80 | 1.80 |
| 1¼ | 4.00 | 0.80 |
| 2½ | 5.20 | 0.80 |
| 5 | 7.00 | 0.00 |
| 7½ | 8.02 | 0.00 |
| 10 | 8.90 | 0.20 |
| 15 | 10.00 | 0.48 |
| 20 | 10.75 | 0.80 |
| 30 | 11.18 | 1.85 |
| 40 | 10.95 | 2.80 |
| 50 | 9.90 | 3.20 |
| 60 | 8.50 | 3.90 |
| 70 | 7.00 | 3.30 |
| 80 | 5.00 | 2.70 |
| 90 | 3.00 | 1.40 |
| 95 | 1.82 | 0.80 |
| 100 | 0.40 | 0.40 |

REFERENCE NO. 853




| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.50 | 1.50 |
| 1¼ | 3.50 | 0.88 |
| 2½ | 4.55 | 0.80 |
| 5 | 6.00 | 0.20 |
| 7½ | 7.00 | 0.00 |
| 10 | 7.80 | 0.15 |
| 15 | 8.60 | 0.63 |
| 20 | 9.15 | 1.10 |
| 30 | 10.00 | 2.00 |
| 40 | 9.30 | 2.80 |
| 50 | 9.00 | 3.00 |
| 60 | 8.00 | 3.05 |
| 70 | 6.80 | 3.00 |
| 80 | 4.90 | 2.05 |
| 90 | 2.90 | 1.20 |
| 95 | 1.90 | 0.40 |
| 100 | 0.25 | 0.25 |

REFERENCE NO. 854




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.87 | 0.87 |
| 1¼ | 2.15 | 0.08 |
| 2½ | 2.85 | 0.00 |
| 5 | 3.90 | 0.27 |
| 7½ | 4.65 | 0.75 |
| 10 | 5.25 | 1.12 |
| 15 | 5.90 | 1.75 |
| 20 | 6.12 | 1.87 |
| 30 | 6.10 | 1.67 |
| 40 | 5.80 | 1.30 |
| 50 | 5.07 | 0.90 |
| 60 | 4.37 | 0.50 |
| 70 | 3.50 | 0.12 |
| 80 | 2.62 | 0.00 |
| 90 | 1.57 | 0.00 |
| 95 | 1.10 | 0.01 |
| 100 | 0.60 | 0.37 |

REFERENCE NO. 855




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.95 | 0.95 |
| 1¼ | 2.00 | 0.25 |
| 2½ | 2.50 | 0.10 |
| 5 | 3.87 | 0.00 |
| 7½ | 4.90 | 0.00 |
| 10 | 5.81 | -0.15 |
| 15 | 7.15 | 0.36 |
| 20 | 8.07 | 0.40 |
| 30 | 8.60 | 0.65 |
| 40 | 8.30 | 0.90 |
| 50 | 7.50 | 1.02 |
| 60 | 6.50 | 1.12 |
| 70 | 5.25 | 1.00 |
| 80 | 3.81 | 0.75 |
| 90 | 2.15 | 0.37 |
| 95 | 1.35 | 0.25 |
| 100 | 0.10 | 0.10 |

REFERENCE NO.856




| % | UP'R | LW'R |
|---|---|---|
| 0 | 3.15 | 3.15 |
| 1¼ | 4.30 | 2.15 |
| 2½ | 4.60 | 1.70 |
| 5 | 5.81 | 1.12 |
| 7½ | 6.50 | 0.55 |
| 10 | 7.05 | 0.52 |
| 15 | 7.80 | 0.15 |
| 20 | 8.28 | 0.10 |
| 30 | 8.50 | 0.60 |
| 40 | 8.30 | 0.81 |
| 50 | 7.55 | 0.82 |
| 60 | 6.70 | 0.77 |
| 70 | 5.62 | 0.62 |
| 80 | 4.25 | 0.45 |
| 90 | 2.70 | 0.25 |
| 95 | 1.88 | 0.18 |
| 100 | 0.40 | 0.40 |

Name of section: I. S. A. 881a
Size of model: 23.62" x 3.937"
Wind velocity: 65.6 ft./sec.
Where tested: I. S. A. Date: 1921

REFERENCE NO.857




| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.75 | 1.75 |
| 1¼ | 3.30 | 0.98 |
| 2½ | 4.00 | 0.62 |
| 5 | 5.25 | 0.31 |
| 7½ | 6.20 | 0.20 |
| 10 | 6.88 | 0.07 |
| 15 | 7.78 | 0.00 |
| 20 | 8.40 | 0.15 |
| 30 | 8.50 | 0.62 |
| 40 | 8.15 | 1.00 |
| 50 | 7.50 | 1.07 |
| 60 | 6.50 | 0.85 |
| 70 | 5.18 | 0.55 |
| [illegible] | 3.77 | 0.25 |
| [illegible] | 2.25 | 0.10 |
| 95 | 1.50 | 0.00 |
| 100 | 0.30 | 0.30 |

Name of section: I. S. A. 881b
Size of model: 23.62" x 3.937"
Wind velocity: 65.6 ft./sec.
Where tested: I. S. A. Date: 1921

REFERENCE NO. 858




| % | UP'R | LW'R |
|---|---|---|
| 0 | 0.75 | 0.75 |
| 1¼ | 2.65 | 0.09 |
| 2½ | 3.50 | 0.00 |
| 5 | 5.35 | 0.15 |
| 7½ | 6.40 | 0.15 |
| 10 | 7.15 | 0.35 |
| 15 | 8.50 | 0.73 |
| 20 | 9.23 | 0.92 |
| 30 | 9.46 | 1.45 |
| 40 | 9.15 | 1.72 |
| 50 | 8.43 | 1.75 |
| 60 | 7.35 | 1.60 |
| 70 | 6.03 | 1.10 |
| 80 | 4.55 | 0.67 |
| 90 | 2.37 | 0.20 |
| 95 | 1.70 | 0.00 |
| 100 | 0.40 | 0.40 |

Name of section: I. S. A. 881c
Size of model: 23.62" x 3.937"
Wind velocity: 65.6 ft./sec.
Where tested: I. S. A. Date: 1921

REFERENCE NO.859




| % | UP'R | LW'R |
|---|---|---|
| 0 | 1.37 | 1.37 |
| 1¼ | 3.60 | 0.40 |
| 2½ | 5.00 | 0.18 |
| 5 | 7.02 | 0.00 |
| 7½ | 8.60 | 0.00 |
| 10 | 9.97 | 0.00 |
| 15 | 11.98 | 0.05 |
| 20 | 13.34 | 0.12 |
| 30 | 14.60 | 0.25 |
| 40 | 14.51 | 0.30 |
| 50 | 13.39 | 0.30 |
| 60 | 11.70 | 0.25 |
| 70 | 9.30 | 0.17 |
| 80 | 7.13 | 0.05 |
| 90 | 4.37 | 0.00 |
| 95 | 2.80 | 0.00 |
| 100 | 1.12 | 0.00 |

Name of section: I. S. A. 911
Size of model: 28.346" x 4.724"
Wind velocity: 65.6 ft./sec.
Where tested: I. S. A. Date: 1922


The lower case
letter adjacent
to the number
represents VI =
c...22.53
n...27.57
r...29.42
u...41.68
v...65.05
Minimum $C_D$
$L/D$ at 1/4 Maximum $C_L$
Chart No 21
.004
.008
.012
.016
.020
.024
.028
.032
.036
.040
.044
.048
.052
6
8
10
12
14
16
18
20
22
795v 796v
766u
767u 856c
768u
760c to 24.10
811v
851n
857c
827v
838c
774v 813v
683v
821v
770r
784v
799u
802r
788v
828v
804u
829v
781v 792v
791v
820v
782v
841c
793v
761n
858c
819v
773v
855c
776v
769r
803r
859c
762n
830v
780v
772v 779v
809v
771v
775v
834v
763r
778v
764r
805r
765m

Chart No 21


The lower case letter adjacent to the number represents VI=
c...22.53
n...27.57
r...29.42
u...41.68
v...65.05
Maximum $C_L$
Mean Spar Depth

Chart No. 22


The lower case letter adjacent to the number represents Vl =
o...22.53
n...27.57
r...29.42
u...41.68
v...65.08
Maximum $C_L$
Maximum $L/D$
760n to 32.60

Chart No. 23


The lower case letter adjacent to the number represents Vl =
o...22.83
n...27.57
r...29.42
u...41.68
v...65.05
Maximum $C_L$
$L/D$ at 2/3 Maximum $C_L$
1.8
1.7
1.6
1.5
1.4
1.3
1.2
1.1
1.0
.9
.8
.7
8
10
12
14
16
18
20
22
24
805r
819v
768n
784r
823v
811v
760n
802r
795v
796v
851n
767u
768u
788u
858c
857c
803r
799u
762n
806n
770r

Chart No. 24

ADDITIONAL COPIES
OF THIS PUBLICATION MAY BE PROCURED FROM
THE SUPERINTENDENT OF DOCUMENTS
U.S.GOVERNMENT PRINTING OFFICE
WASHINGTON, D. C.
AT
20 CENTS PER COPY




Positive directions of axes and angles (forces and moments) are shown by arrows

| Axis | | Force (parallel to axis) symbol | Moment about axis | | | Angle | | Velocities | |
|---|---|---|---|---|---|---|---|---|---|
| Designation | Symbol | | Designation | Symbol | Positive direction | Designation | Symbol | Linear (component along axis) | Angular |
| Longitudinal | $X$ | $X$ | rolling | $L$ | $Y \longrightarrow Z$ | roll | $\Phi$ | $u$ | $p$ |
| Lateral | $Y$ | $Y$ | pitching | $M$ | $Z \longrightarrow X$ | pitch | $\Theta$ | $v$ | $q$ |
| Normal | $Z$ | $Z$ | yawing | $N$ | $X \longrightarrow Y$ | yaw | $\Psi$ | $w$ | $r$ |

Absolute coefficients of moment

$$C_L = \frac{L}{qbS} \quad C_M = \frac{M}{qcS} \quad C_N = \frac{N}{qfS}$$

Angle of set of control surface (relative to neutral position), $\delta$. (Indicate surface by proper subscript.)

## 4. PROPELLER SYMBOLS

$D$, Diameter.
$p_e$, Effective pitch
$p_g$, Mean geometric pitch.
$p_s$, Standard pitch.
$p_v$, Zero thrust.
$p_a$, Zero torque.
$p/D$, Pitch ratio.
$V'$, Inflow velocity.
$V_s$, Slip stream velocity.

$T$, Thrust.
$Q$, Torque.
$P$, Power.
(If "coefficients" are introduced all units used must be consistent.)
$\eta$, Efficiency $= T\,V/P$.
$n$, Revolutions per sec., r. p. s.
$N$, Revolutions per minute., R. P. M.
$\Phi$, Effective helix angle $= \tan^{-1}\left(\frac{V}{2\pi rn}\right)$

## 5. NUMERICAL RELATIONS

1 HP = 76.04 kg/m/sec. = 550 lb./ft./sec.
1 kg/m/sec. = 0.01315 HP.
1 mi./hr. = 0.44704 m/sec.
1 m/sec. = 2.23693 mi./hr.

1 lb. = 0.4535924277 kg.
1 kg = 2.2046224 lb.
1 mi. = 1609.35 m = 5280 ft.
1 m = 3.2808333 ft.